

Model IQ 50

Deluxe slimline telephone



IQ50G
Granite Grey

Feature List

- Backlit keypad
- Tone dialling
- Large keys for easy use
- 100mS PBX Recall & Pause/Redial keys
- Ringer volume control & ringer light
- Wall Bracket included
- Six (6) Year parts and labour warranty
- Rugged durable construction
- Noise cancelling handset microphone



IQ50C
Cream

More Features

- Hearing aid compatible
- Individual serial no. on each unit
- Built-in message waiting and ringer indicator lamp
- Keypad and Line Reset button located on the handset
- Available in Granite Grey and Cream
- Message waiting light built-in to suit many popular PABXs and optional add-ons to suit many others
- 'Tropicguard' protection for humid conditions such as hotel bathrooms
- Dialless version available for hotline, hotel lobby or information booth application



Specifications of Interquartz IQ 50

Dial mode	Tone (DTMF) signaling system conforms to CCITT Recommendation Q.23: Frequency Deviation <1.5%; Total Distortion Product <10%; Digit (Tone) Duration >85msec.; Interdigit Pause >85 msec.
PBX Recall	100 milliseconds Timed Break
Message Waiting light	80 – 120VDC either constant or flashing. Suits: Ericsson BP250 (except IQ 50), Alcatel, Exicom, Panasonic, Fujitsu, NEC, Nortel, Nitsuko, Samsung, Lucent Index and Hybrex Optional: AT&T, Siemens ISDX, Siemens HICOM, Panasonic TD1232, Ericsson MD110 and some Hybrex
Ringer Lamp	Neon tube
Dimensions	Width: 68mm; Length: 222mm; Height: 73mm
Ringer	Electronic, with Hi/Lo/Off settings; 80dBA minimum at a distance of 30 cm.
Weight	The weight of the unit is 0.6 kg, approximately
Line cord and Plug	3m RJ12 to RJ45 with optional 603, RJ11 or RJ12
Wall mount kit	Included
Operating Temp and Humidity	Temperature : 0°C - 40°C; Humidity : 95% RH max, No dew forming
Regulatory Compliance	Complies with current ACA/Austel standards
Acoustic Shock Protection	Instantaneous – 76dBA (ACA standard 123dB SPL) Continuous – 103dBA (ACA standard 120dBA)
Colour	Granite Grey (IQ50G) & Cream (IQ50C) - ABS plastic